

Flake ice maker "COM-50", "COM-85" and "COM-150"



"COM-50" MODEL: PRODUCTION 58 kg-24 HOURS.
"COM-85" MODEL: PRODUCTION 89 kg-24 HOURS.
"COM-150" MODEL: PRODUCTION 142 kg-24 HOURS.

APPLICATIONS

For preservation and storage of analytic samples, biological tissues, cellular cultures and other applications that require maintenance of the temperature below ambient.

FEATURES

External case made of stainless steel.

Thermal isolated inside.

High capacity for flake ice production from running or purified

Tropicalized (Class T).

The installation of an anti-scale filter and periodic cleaning are advised in areas with

medium or high limescale content (hard water)

CONTROL PANEL

Main power switch.



MODELS	Código	Production Kg (24h.)	Capacity Kg (tank)	Height / Width / Depth cm	Power supply	Power W	Weight Kg
COM-50	5020104	58	20	79 47 60	220V 50hz	470	58
COM-85	5020105	89	20	79 47 60	220V 50hz	550	58
COM-150	5020106	142	60	136 51 55	220V 50hz	900	75

COMPLEMENT "ICE BUCKET"

See page 190



Manual hidraulic press "PM-15"

MAXIMUM PRESSURE LOAD: 15 TONS

FEATURES

Compact and easy to use, designed for a maximum pressure load of 15 tons, especially for pressing in chemical research laboratories and materials for preparing ceramic composite. This machine has an integrated auto return hydraulic pump.

Tablets from 6.3mm to 19mm can be compacted with the MT matrix accessory, for KBR compression technique and fluorescence analysis works. Cylinder elevation of 0-25mm.

MODEL

Part No.	Max. Pressure tons	Height	/ Widtl mm	n / Depth	Weight Kg	Max. Working area mm Height / Width / Depth
5810200	15	55	13	21	30	150 x 160 x 160

ACCESORIES

Part No. 5810201 MT Matrix 12.5mm
Part No. 5810202 MT Matrix 6.3mm
Part No. 5810203 MT Matrix 19mm
Part No. 5810204 MT Matrix 3.2mm





