

## **Compact Vertical Laminar Flow Bench**



# Telstar Mini-V/PCR, The UltraCompact Vertical Flow Bench

A quiet blower delivers an ultra clean laminar airflow over the working bench to protect manipulated products from dust, from environment contamination and from cross contamination in the working area.

Vertical benches are ideal solution for the handling of non hazardous biological samples.

Moreover Telstar **Mini-V/PCR** features a built-in UV light with timer particularly suitable for PCR process to denaturate oligonucleotide contaminants.

#### **General features**

- Bench top cabinet with non recirculated vertical laminar flow.
- Compact dimensions compatible with all laboratory doors and dimensions.
- Epoxy powder coated finish zinctec steel cabinet.
- AISI 304 stainless steel work bench.
- H14 HEPA filter easily accessible for replacement.
- Prefilter 85% ASHRAE, in the inlet side.
- Class 3 according ISO 14644-1; Grade A Annex 1 GMP.
- Very low power consumption, with EC blower and LED lighting: 66W

### **Control** system

An intuitive electronic control system offers fast and complete control over all cabinet functions.

- Alphanumerical LCD display (1) indicates:
  - Airflow status: Full speed or half speed.
  - U.V. count down timer.
  - Total running hours of the cabinet and UV light running hours.
- Function scrolling keys (2).
- Full speed/half speed selection key with LED (3).
- Light ON/OFF key and LED (4).
- UV Light ON/OFF key and LED (5).
- Activation key of optional electrical equipment (6).
- UV "ON" alarm LED (7).







CHINA No. 30 Jin Wen Road, Zu Qiao Airport Industrial Park, Pudong District 201323 Shangai T +86 21 58 093 731 F +86 21 58 092 857

#### Technical data

As standard, **Mini-V/PCR** includes LED light, built-in UV-light with timer, electrical socket in working area, stainless steel bench.

230V/50Hz (other voltage upon request).

External dimensions (W x D x H):  $670 \times 520 \times 1.125$  mm. Internal dimensions (W x D x H):  $630 \times 500 \times 570$  mm. Weight: 70 Kg.

Lighting > 750 lux / noise level: 56 dBA.

#### **Options and accessories**

- Gas or vacuum tap.
- Pipette holder (2).
- Front closure UV safe (3).
- Filter clogging alarm.
- Thermoanemometric air speed sensor to monitor laminar flow speed and to provide filter clogging alarm



ISO 9001: Certified Company

Telstar reserves the right to improvements and specification changes without notice.

 SPAIN

 Headquarters

 Av. Font i Sagué, 55

 08227 Terrassa (Spain)

 T +34 937 361 600

 F +34 937 861 380

Santibáñez de Béjar, 3 08042 Madrid T +34 913 717 790 F +34 913 717 791

www.telstar.com sales.laboratory@telstar.com

NORTH AMERICA 1504 Grundy's Lane Bristol PA 19007 T +1 (215) 826 0770 F +1 (215) 826 0222

JAPAN Azbil Corporation

#### Azbil Corporation Tokyo Building, 2-7-3 Marunouchi, Chiyoda-ku, Tokyo 100-6419, T +81 3 6810 1000 F +81 3 5220 7270